

DIESEL GENERATOR SET



DE165E0

Image shown may not reflect actual package

Output Ratings		
Generator Set Model - 3 Phase	Prime*	Standby*
400/230 V, 50 Hz	150.0 kVA 120.0 kW	165.0 kVA 132.0 kW
480V, 60 Hz	168.8 kVA 135.0 kW	187.5 kVA 150.0 kW

* Refer to ratings definitions on page 4.
Ratings at 0,8 power factor.

Technical Data		
Engine Make & Model:	Cat® C7.1	
Generator Model:	LC3114J	
Control Panel:	EMCP 4.1	
Base Frame Type:	Heavy Duty Fabricated Steel	
Circuit Breaker Type:	3 Pole MCCB	
Frequency:	50 Hz	60 Hz
Engine Speed: RPM	1500	1800
Fuel Tank Capacity: litres (US gal)	349 (92.2)	
Fuel Consumption, Prime: l/hr (US gal/hr)	32.4 (8.6)	37.5 (9.9)
Fuel Consumption, Standby : l/hr (US gal/hr)	35.1 (9.3)	41.1 (10.9)



DIESEL GENERATOR SET

Engine Technical Data

Physical Data		50 Hz		60 Hz	
Manufacturer:	Caterpillar				
Model:	C7.1				
No. of Cylinders/Alignment:	6 / In Line				
Cycle:	4 Stroke				
Induction:	Turbocharged Air To Air Charge Cooled				
Cooling Method:	Water				
Governing Type:	Mechanical				
Governing Class:	ISO 8528 G2				
Compression Ratio:	16.0:1				
Displacement: l (cu.in)	7.0 (427.8)				
Bore/Stroke: mm (in)	105.0 (4.1)/135.0 (5.3)				
Moment of Inertia: kg m² (lb. in²)	1.53 (5228)				
Engine Electrical System:					
-Voltage/Ground:	12/Negative				
-Battery Charger Amps:	85				
Weight: kg (lb) - Dry:	788 (1737)				
- Wet:	822 (1812)				

Air System		50 Hz		60 Hz	
Air Filter Type:	Paper Element				
Combustion Air Flow:					
m ³ /min (cfm)					
-Standby:	10.7 (377)	15.0 (529)			
-Prime:	10.0 (354)	14.4 (509)			
Max. Combustion Air Intake					
Restriction: kPa (in H₂O)	3.0 (12.0)	3.0 (12.0)			
Radiator Cooling Air Flow:					
m ³ /min (cfm)	303.4 (10714)	239.4 (8454)			
External Restriction to					
Cooling Air Flow: Pa (in H₂O)	125 (0.5)	125 (0.5)			

Cooling System		50 Hz		60 Hz	
Cooling System Capacity:					
l (US gal)		21.0 (5.5)	21.0 (5.5)		
Water Pump Type:	Centrifugal				
Heat Rejected to Water & Lube Oil: kW (Btu/min)					
-Standby:	75.7 (4305)	80.1 (4555)			
-Prime:	69.1 (3930)	73.5 (4180)			
Heat Radiation to Room: Heat radiated from engine and alternator					
kW (Btu/min)					
-Standby:	22.4 (1274)	23.4 (1331)			
-Prime:	19.9 (1132)	20.8 (1183)			
Radiator Fan Load: kW (hp)	4.5 (6.0)	8.0 (10.7)			

Cooling system designed to operate in ambient conditions up to 50°C (122°F). Contact your local Cat dealer for power ratings at specific site conditions.

Lubrication System		50 Hz		60 Hz	
Oil Filter Type:	Spin-On, Full Flow				
Total Oil Capacity l (US gal):	16.5 (4.4)				
Oil Pan l (US gal):	14.9 (3.9)				
Oil Type:	API CH4 / CI4 15W-40				
Cooling Method:	Water				

Performance		50 Hz		60 Hz	
Engine Speed: RPM		1500	1800		
Gross Engine Power: kW (hp)					
-Standby:	149.1 (200.0)	171.8 (230.0)			
-Prime:	136.0 (182.0)	155.4 (208.0)			
BMEP: kPa (psi)					
-Standby:	1701.0 (246.7)	1633.0 (236.8)			
-Prime:	1551.0 (225.0)	1477.0 (214.2)			
Regenerative Power: kW	6.7	7.7			

Fuel System		50 Hz		60 Hz	
Fuel Filter Type:	Replaceable Element				
Recommended Fuel:	Class A2 Diesel or BSEN590				
Fuel Consumption: l/hr (US gal/hr)					
		110% Load	100% Load	75% Load	50% Load
Prime					
50 Hz	35.1 (9.3)	32.4 (8.6)	24.9 (6.6)	16.6 (4.4)	
60 Hz	41.1 (10.9)	37.5 (9.9)	28.9 (7.6)	19.7 (5.2)	
Standby					
50 Hz		35.1 (9.3)	27.2 (7.2)	18.3 (4.8)	
60 Hz		41.1 (10.9)	31.9 (8.4)	21.8 (5.8)	

(based on diesel fuel with a specific gravity of 0.85 and conforming to BS2869, Class A2)

Exhaust System		50 Hz		60 Hz	
Silencer Type:	-				
Silencer Model & Quantity:	EXSY1 (-)				
Pressure Drop Across					
Silencer System: kPa (in Hg)		-	-		
Silencer Noise Reduction					
Level: dB		-	-		
Max. Allowable Back					
Pressure: kPa (in. Hg)		6.0 (1.8)	6.0 (1.8)		
Exhaust Gas Flow:					
m ³ /min (cfm)					
-Standby:	25.5 (902)	32.2 (1137)			
-Prime:	23.9 (843)	31.9 (1125)			
Exhaust Gas Temperature: °C (°F)					
-Standby:	484 (903)	407 (765)			
-Prime:	484 (903)	407 (765)			

DIESEL GENERATOR SET



Generator Performance Data

Data Item	50 Hz				60 Hz				
	415/240V	400/230V 230/115V 200/115V	380/220V 220/110V	220/127V	480/277V 240/139V	380/220V 220/110V	240/120V 208/120V		440/254V 220/127V
Motor Starting Capability* kVA	414	390	358	455	452	307	358	-	393
Short Circuit Capacity** %	300	300	300	300	300	300	300	-	300
Reactances: Per Unit									
Xd	2.834	3.050	3.380	2.185	2.860	4.326	3.808	-	3.404
X'd	0.136	0.147	0.163	0.105	0.138	0.208	0.183	-	0.164
X''d	0.082	0.088	0.098	0.063	0.083	0.125	0.110	-	0.098

Reactances shown are applicable to prime ratings.

*Based on 30% voltage dip at 0.6 power factor and SHUNT excitation system.

** With optional Permanent Magnet generator.

Generator Technical Data

Physical Data	
LC Series	
Model:	LC3114J
No. of Bearings:	1
Insulation Class:	H
Winding Pitch - Code:	2/3 - 6
Wires:	12
Ingress Protection Rating:	IP23
Excitation System:	SHUNT
AVR Model:	R250

Operating Data	
Overspeed: RPM	2250
Voltage Regulation: (steady state)	+/- 0.5%
Wave Form NEMA = TIF:	50
Wave Form IEC = THF:	2.0%
Total Harmonic Content LL/LN:	2.0%
Radio Interference:	Suppression is in line with European Standard EN61000-6
Radiant Heat: kW (Btu/min)	
-50 Hz:	10.2 (580)
-60 Hz:	11.1 (631)

DIESEL GENERATOR SET



Technical Data


Voltage 50 Hz	Prime		Standby	
	kVA	kW	kVA	kW
415/240V	150.0	120.0	165.0	132.0
400/230V	150.0	120.0	165.0	132.0
380/220V	150.0	120.0	165.0	132.0
230/115V	150.0	120.0	165.0	132.0
220/127V	130.0	104.0	143.0	114.4
220/110V	150.0	120.0	165.0	132.0
200/115V	150.0	120.0	165.0	132.0

Voltage 60 Hz	Prime		Standby	
	kVA	kW	kVA	kW
480/277V	168.8	135.0	187.5	150.0
220/127V	168.8	135.0	187.5	150.0
380/220V	160.0	128.0	176.0	140.8
240/120V	168.8	135.0	187.5	150.0
440/254V	-	-	-	-
220/110V	160.0	128.0	176.0	140.8
208/120V	168.8	135.0	187.5	150.0
240/139V	168.8	135.0	187.5	150.0

Weights & Dimensions

Weights: kg (lb)	
Net (+ lube oil)	1610 (3549)
Wet (+ lube oil & coolant)	1631 (3596)
Fuel, lube oil & coolant	1927 (4247)

Dimensions: mm (in)	
Length	2500 (98.4)
Width	1120 (44.1)
Height	1528 (60.2)



Note: General configuration not to be used for installation. See general dimension drawings for detail.

Definitions

Standby Rating

Output available with varying load for the duration of the interruption of the normal source power. Average power output is 70% of the standby power rating. Typical operation is 200 hours per year, with maximum expected usage of 500 hours per year.

Prime Rating

Output available with varying load for an unlimited time. Average power output is 70% of the prime power rating. Typical peak demand is 100% of prime rated kW with 10% overload capability for emergency use for a maximum of 1 hour in 12. Overload operation cannot exceed 25 hours per year.

Standard Reference Conditions

Note: Standard reference conditions 25°C (77°F) air inlet temp, 100m (328ft) A.S.L. 30% relative humidity. Fuel consumption data at full load with diesel fuel with specific gravity of 0.85 and conforming to BS2869: 1998, Class A2.

General Data

Documents

A full set of operation and maintenance manuals and circuit wiring diagrams.

Quality Standards

The equipment meets the following standards: IEC60034-1, IEC60034-22, ISO3046, ISO8528, NEMA MG 1-32, NEMA MG 1-33, 2004/108/EC, 2006/42/EC, 2006/95/EC.