

DIESEL GENERATOR SET



DE200E0

Image shown may not reflect actual package

Output Ratings		
Generator Set Model - 3 Phase	Prime*	Standby*
400/230 V, 50 Hz	180.0 kVA 144.0 kW	200.0 kVA 160.0 kW
	-	-

* Refer to ratings definitions on page 4.
Ratings at 0.8 power factor.

Technical Data		
Engine Make & Model:	Cat® C7.1	
Generator Model:	LC5014D	
Control Panel:	EMCP 4.1	
Base Frame Type:	Heavy Duty Fabricated Steel	
Circuit Breaker Type:	3 Pole MCCB	
Frequency:	50 Hz	60 Hz
Engine Speed: RPM	1500	-
Fuel Tank Capacity: litres (US gal)	418 (110.4)	
Fuel Consumption, Prime: l/hr (US gal/hr)	40.2 (10.6)	-
Fuel Consumption, Standby : l/hr (US gal/hr)	43.8 (11.6)	-

DIESEL GENERATOR SET



Engine Technical Data

Physical Data		Lubrication System	
Manufacturer:	Caterpillar	Oil Filter Type:	Spin-On, Full Flow
Model:	C7.1	Total Oil Capacity I (US gal):	16.5 (4.4)
No. of Cylinders/Alignment:	6 / In Line	Oil Pan I (US gal):	14.9 (3.9)
Cycle:	4 Stroke	Oil Type:	API CH4 / C14 15W-40
Induction:	Turbocharged Air To Air Charge Cooled	Cooling Method:	Water
Cooling Method:	Water	Performance	
Governing Type:	Mechanical	50 Hz	60 Hz
Governing Class:	ISO 8528 G2	Engine Speed: RPM	1500 -
Compression Ratio:	16.0:1	Gross Engine Power: kW (hp)	
Displacement: I (cu.in)	7.0 (427.8)	-Standby:	185.5 (249.0) -
Bore/Stroke: mm (in)	105.0 (4.1)/135.0 (5.3)	-Prime:	167.6 (225.0) -
Moment of Inertia: kg m² (lb. in²)	1.26 (4306)	BMEP: kPa (psi)	
Engine Electrical System:		-Standby:	2116.0 (306.9) -
-Voltage/Ground:	12/Negative	-Prime:	1912.0 (277.3) -
-Battery Charger Amps:	85	Regenerative Power: kW	0.0 -
Weight: kg (lb) - Dry:	788 (1737)	Fuel System	
- Wet:	822 (1812)	Fuel Filter Type:	Replaceable Element
		Recommended Fuel:	Class A2 Diesel or BSEN590
		Fuel Consumption: l/hr (US gal/hr)	
		110% Load	100% Load
		75% Load	50% Load
		Prime	
		50 Hz	43.8 (11.6), 40.2 (10.6), 30.9 (8.2), 19.7 (5.2)
		60 Hz	-
		Standby	
		50 Hz	43.8 (11.6), 34.2 (9.0), 22.3 (5.9)
		60 Hz	-
		(based on diesel fuel with a specific gravity of 0.85 and conforming to BS2869, Class A2)	
Air System	50 Hz	60 Hz	
Air Filter Type:	Paper Element		
Combustion Air Flow:			
m ³ /min (cfm)	-Standby: 13.9 (490)	-	
	-Prime: 13.0 (457)	-	
Max. Combustion Air Intake			
Restriction: kPa (in H₂O)	3.0 (12.0)	-	
Radiator Cooling Air Flow:			
m ³ /min (cfm)	307.2 (10849)	-	
External Restriction to			
Cooling Air Flow: Pa (in H₂O)	125 (0.5)	-	
Cooling System	50 Hz	60 Hz	
Cooling System Capacity:			
I (US gal)	27.0 (7.1)	-	
Water Pump Type:	Centrifugal		
Heat Rejected to Water & Lube Oil: kW (Btu/min)			
-Standby:	76.4 (4345)	-	
-Prime:	74.2 (4220)	-	
Heat Radiation to Room: Heat radiated from engine and alternator			
kW (Btu/min)	-Standby: 37.6 (2140)	-	
	-Prime: 34.1 (1938)	-	
Radiator Fan Load: kW (hp)	6.3 (8.5)	-	
Cooling system designed to operate in ambient conditions up to 50°C (122°F). Contact your local Cat dealer for power ratings at specific site conditions.			
Exhaust System	50 Hz	60 Hz	
Silencer Type:	Industrial		
Silencer Model & Quantity:	EXSY1 (1)		
Pressure Drop Across			
Silencer System: kPa (in Hg)	3.50 (1.034)	-	
Silencer Noise Reduction			
Level: dB	10	-	
Max. Allowable Back			
Pressure: kPa (in. Hg)	6.0 (1.8)	-	
Exhaust Gas Flow:			
m ³ /min (cfm)	-Standby: 33.9 (1195)	-	
	-Prime: 31.4 (1110)	-	
Exhaust Gas Temperature: °C (°F)			
-Standby:	538 (1000)	-	
-Prime:	489 (912)	-	

DIESEL GENERATOR SET



Generator Performance Data

Data Item	50 Hz				60 Hz				
	415/240V	400/230V 230/115V 200/115V	380/220V 220/110V	220/127V					
Motor Starting Capability* kVA	352	331	302	389	-	-	-	-	-
Short Circuit Capacity** %	300	300	300	300	-	-	-	-	-
Reactances: Per Unit									
Xd	2.885	3.105	3.440	2.281	-	-	-	-	-
X'd	0.146	0.158	0.175	0.116	-	-	-	-	-
X''d	0.088	0.095	0.105	0.069	-	-	-	-	-

Reactances shown are applicable to prime ratings.

*Based on 30% voltage dip at 0.6 power factor and SHUNT excitation system.

** With optional Permanent Magnet generator

Generator Technical Data

Physical Data	
LC Series	
Model:	LC5014D
No. of Bearings:	1
Insulation Class:	H
Winding Pitch - Code:	2/3 - 6
Wires:	12
Ingress Protection Rating:	IP23
Excitation System:	SHUNT
AVR Model:	R250

Operating Data	
Overspeed: RPM	2250
Voltage Regulation: (steady state)	+/- 0.5%
Wave Form NEMA = TIF:	50
Wave Form IEC = THF:	2.0%
Total Harmonic Content LL/LN:	4.0%
Radio Interference:	Suppression is in line with European Standard EN61000-6
Radiant Heat: kW (Btu/min)	
-50 Hz:	13.2 (751)
-60 Hz:	-

DIESEL GENERATOR SET



Technical Data


Voltage 50 Hz	Prime		Standby	
	kVA	kW	kVA	kW
415/240V	180.0	144.0	199.8	159.8
400/230V	180.0	144.0	200.0	160.0
380/220V	180.0	144.0	199.8	159.8
230/115V	180.0	144.0	200.0	160.0
220/127V	160.0	128.0	176.0	140.8
220/110V	180.0	144.0	199.8	159.8
200/115V	180.0	144.0	200.0	160.0

Voltage 60 Hz	Prime		Standby	
	kVA	kW	kVA	kW

Weights & Dimensions

Weights: kg (lb)	
Net (+ lube oil)	1691 (3728)
Wet (+ lube oil & coolant)	1718 (3788)
Fuel, lube oil & coolant	2072 (4568)

Dimensions: mm (in)	
Length	2500 (98.4)
Width	1320 (52.0)
Height	1626 (64.0)



Note: General configuration not to be used for installation. See general dimension drawings for detail.

Definitions

Standby Rating

Output available with varying load for the duration of the interruption of the normal source power. Average power output is 70% of the standby power rating. Typical operation is 200 hours per year, with maximum expected usage of 500 hours per year.

Prime Rating

Output available with varying load for an unlimited time. Average power output is 70% of the prime power rating. Typical peak demand is 100% of prime rated kW with 10% overload capability for emergency use for a maximum of 1 hour in 12. Overload operation cannot exceed 25 hours per year.

Standard Reference Conditions

Note: Standard reference conditions 25°C (77°F) air inlet temp, 100m (328ft) A.S.L. 30% relative humidity. Fuel consumption data at full load with diesel fuel with specific gravity of 0.85 and conforming to BS2869: 1998, Class A2.

General Data

Documents

A full set of operation and maintenance manuals and circuit wiring diagrams.

Quality Standards

The equipment meets the following standards: IEC60034-1, IEC60034-22, ISO3046, ISO8528, NEMA MG 1-32, NEMA MG 1-33, 2004/108/EC, 2006/42/EC, 2006/95/EC.